



Material : Phosphor Bronze
 Thickness : 0.2mm
 Plating : Tin plated
 Wire Range : Suitable for AWG 24~28
 Insulation Diameter : \varnothing 1.9mm Max.
 Reel Q'ty : 10,000 pc / Reel

UNIT: mm

T 2530 — T P L 0 0 0 0 0 R

- | | | |
|------------------------------|---|----------------------|
| 1. PRODUCTS:
T:Terminal | 4. MATERIAL:
P:Phosphor Bronze | 7. FILL IT WITH "0" |
| 2. SERIES NO.:
2530 | 5. WIRE OPTION:
L:Suitable For 24~28 Awg | 8. FILL IT WITH "0" |
| 3. CONTACT PLATING:
T:Tin | 6. FILL IT WITH "0" | 9. FILL IT WITH "0" |
| | | 10. FILL IT WITH "0" |
| | | 11. R:ROHS |

RoHS Compliant	HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
	APPD. 核准	TOLERANCE 容許公差 .0 ± .00 ± ANG. ±
DWG. Hedy	SCALE 比例 參考	SIZE. 紙張尺寸 A 4
DATE 制表日 2012/07/10	UNIT 單位 MM	REV. 版次 A
PAGE 張數 1 / 1	PART NO. 料號 T2530-TPL00000R	