



PC BOARD LAYOUT

MATERIALS AND FINISH

HOUSING—PBT POLYESTER UL-94V-0 MIXED GLASS FIBER.
 STANDARD COLOR FIBER.
 CONTACT—0.45mm DIAMETER PHOS-BRONZE
 PLATED WITH HARD GOLD.
 SHIELD:0.25mm THICK COPPER ALLOY PLATED WITH NICKEL.

ELECTRICAL:

- 1.CURRENT RATING: 1.5 AMP
- 2.VOLTAGE RATING: 150 VAC
- 3.CONTACT RESISTANCE: 20 MILLIOHMS MAX
- 4.INSULATION RESISTANCE: 500 MILLIOHMS MIN
- 5.DIELECTRIC WITHSTANDING VOLTAGE: 1000 VAC, 1MIN

RoHS
Compliant

HSM 玄茂科技股份有限公司
HSUAN MAO TECHNOLOGY CO., LTD.

APPD. 核准 *Judie*
 DWG. 製圖 *Jolin*
 DATE 制表日 2006/09/29

SCALE 比例 參考
 UNIT 單位 M M
 PAGE 張數 1 OF 1

TOLERANCE 容許公差
 .000 ±0.13 ANG±3°
 .00 ±0.25
 .0 ±0.38
 SIZE 紙張尺寸 A 4
 REV. 版本 A

PART NAME 品名
 SIDE ENTRY PCB JACK STAMPED PIN 8P8C GANG TYPE
 4 JACKS FULLY SHIELDED C TYPE BLACK COLOR
 ROHS LOW-LEAD

PART NO. 料號 C0060-88DCXB00R