



MATERIAL: HOUSING-PBT POLYESTER UL-94V-0
 MIXED GLASS FIBER,
 STANDARD COLOR-BLACK
 CONTACTS-0.35mm THICK PHOS-BRONZE
 PLATED WITH HARD GOLD AND
 GOLD FLASH IN SOLDER AREA.
 SHIELD-0.25mm THICK COPPER ALLOY,
 PLATED WITH NICKEL.
 CAVITY CONFIRMS TO FCC RULES AND REGULATIONS
 PART 68,SUBPART F.

PC BOARD LAYOUT

| | | | |
|-----------------------|-------------|---|---|
| RoHS Compliant | | HSM 玄茂科技股份有限公司 | |
| | | HSUAN MAO TECHNOLOGY CO., LTD. | |
| APPD. 核准 | SCALE 比例 | TOLERANCE .000 ±0.13 .00 ±0.25 .0 ±0.38 °ANG±3° | PART NAME 品名 |
| DWG. 製圖 | Hedy | UNIT 單位 | STACKED PCB JACK FLAT PIN 8P8C 2X3P GANG TYPE SHIELDED THREE TABS ROHS |
| DATE 制表日 | 2016/06/20 | MM | PART NO. |
| | | PAGE 張數 | 料號 |
| | | 1 / 1 | C0061-88FYXB10R |
| | | REV. 版次 | |
| | | A | |