



MATERIALS:

SHIELDED: STAINLESS STEEL.

PLASTIC HOUSING: ENGINEERING THERMOPLASTIC
 FLAMMABILITY RATING UL 94V-0.

CONTACTS: PHOSPHOR BRONZE

PLATING: GOLD PLATING OVER NICKEL IN CONTACT.

SPECIFICATION:

CURRENT RATING: 1.5A

VOLTAGE RATING: 125V AC

DIELECTRIC WITHSTANDING VOLTAGE: 1000V AC, 60Hz, 1min.

INSULATION RESISTANCE: 500MΩ Min.

CONTACT RESISTANCE: 60mΩ Max.

OPERATING TEMPERATURE: 0°C TO +70°C

Single Panel-Latch Clearance
 Panel Thickness 0.062 inch

Front Panel Jack Only Clearance
 W/O Latch Feature

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准		TOLERANCE 容許公差 0 ±0.38 .00 ±0.25 ANG. ±3°	PART NAME 品名 IN LINE COUPLER JACK(CAT5e) 10P8C WITH FULLY SHIELDED WITH P.C.B SELECTIVE GOLD 30U" PLATING BLACK INSULATOR ROHS
DWG. 製圖 HELEN	SCALE 比例 參考	UNIT 單位 MM	PART NO. 料號 C0076-08YIBY00R
DATE 制表日 2016/8/5	PAGE 張數 1 OF 1	REV. 版本 A	