



**MATERIAL AND FINISH**

Housing: Standard Material Glass Filled Polyester UL 94V-0  
 Standard Colour Black.  
 Contact: 0.35mm Thickness Phosphor Bronze,  
 Shielded: 0.20mm Thickness Copper Alloy With Tin/Nickel  
 Plated.  
 Gold Plating: Selective Gold Plating.

**ELECTRICAL:**

- 1. Current Rating : 1.5 AMP
- 2. Voltage Rating : 150 VAC
- 3. Contact Resistance : 20 Milliohms MAX
- 4. Insulation Resistance : 500 Milliohms MIN
- 5. Dielectric Withstanding Voltage : 1000 VAC, 1min

**SUGGESTED PCB LAYOUT  
(COMPONENT SIDE)**

RoHS Compliant		<b>HSM</b> 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 Hedy	SCALE 比例 参考	TOLERANCE 容許公差 .000 ±0.13 .00 ±0.25 .0 ±0.38 ANG ±3°	PART NAME 品名 SIDE ENTRY PCB DIP JACK 10P8C W/ SHIELDED W/SPLIT FOOT FLAT PIN 0.35mm SELECTIVE GOLD 6U" PLATING BLACK INSULATOR ROHS
DWG. 製圖 Yumi	UNIT 單位 MM	SIZE 紙張尺寸 A 4	PART NO. C0077-08PAQB00R
DATE 制表日 2011/01/06	PAGE 張數 1 OF 1	REV. 版次 A	料號 C0077-08PAQB00R