



BAR	No of contacts	Dim A	Dim B
no bar	6	5.08	7.62
no bar	8	7.62	10.16
no bar	10	10.16	12.70
no bar	12	12.70	15.24
no bar	14	15.24	17.78
no bar	16	17.78	20.32
with bar	18	20.32	22.86
with bar	20	22.86	25.40
with bar	22	25.40	27.94
with bar	24	27.94	30.48
with bar	28	33.02	35.56
with bar/2	32	38.10	40.64

Technical Data:

Material:

Insulator body(housing):PBT(black UL-94V0)

Pin(outsleeve): Brass, machined,CuZn38pb2

gold plated: 2um/80u"nickel/full gold-flashed

Clip(4 Finger): Beryllium copper

gold plated: 2um/80u"nickel/full gold-flashed

Electrical

Current rating: 3 Amps/contact max

Insulation resistance: > 1000MΩ at V=100 V

Operating: 60 Veff

Rated voltage: 100 VRms/150 VDC

Machanical:

Operating temperature: Gold plated:-55° C to + 125° C

Soldering temperature : +200 ° C, 10s max.

RoHS
Compliant

HSM 玄茂科技股份有限公司
HSUAN MAO TECHNOLOGY CO., LTD.

APPD. 核准 Betty
DWG. 製圖 Betty
DATE 制表日 2012/02/23

SCALE 比例 參考
UNIT 單位 MM
PAGE 張數 1 OF 1
REV. 版次 A

PART NAME 品名
2.54mm IC SOCKET MACHINED PIN
4 FINGERED CLIP ROW PITCH:0.3"
XXP GOLD PLATING DIP LENGTH 7.4mm ROHS
PART NO. 料號 C0110-XXSABB00R