



BAR	No of contacts	Dim A	Dim B
no bar	6	5.08	7.62
<b>no bar</b>	<b>8</b>	<b>7.62</b>	<b>10.16</b>
no bar	10	10.16	12.70
no bar	12	12.70	15.24
no bar	14	15.24	17.78
no bar	16	17.78	20.32
with bar	18	20.32	22.86
with bar	20	22.86	25.40
with bar	22	25.40	27.94
with bar	24	27.94	30.48
with bar	28	33.02	35.56
with bar/2	32	38.10	40.64

Technical Data:  
 Material:  
 Insulator body(housing):PBT( black UL-94V0)  
 Pin(outsleeve): Brass, machined,CuZn38pb2  
 Tin plated: 2um/80u"nickel,5um/200u" Tin  
 Clip(4 Finger): Beryllium copper  
 gold plated: 2um/80u"nickel/full gold-flashed  
 Electrical  
 Current rating: 3 Amps/contact max  
 Insulation resistance: > 1000MΩ at V=100 V  
 Operating: 60 Veff  
 Mechanical:  
 Operating temperature: Gold plated:-55° C to + 125° C  
 Tin plated: -40° C to +105° C  
 Soldering temperature : +200 ° C, 10s max.

RoHS Compliant		<b>HSM 玄茂科技股份有限公司</b> <b>HSUAN MAO TECHNOLOGY CO., LTD.</b>	
APPD. 核准 Betty		TOLERANCE 容許公差 .0 ± .00 ± ANG. ±	PART NAME 品名 2.54mm IC SOCKET MACHINED PIN 4 FINGERED CLIP ROW PITCH:0.3" XXP PIN:TIN CLIP:GOLD PLATING DIP LENGTH 11.56mm ROHS
DWG. 製圖 Betty	SCALE 比例 參考 UNIT 單位 MM	SIZE. 紙張尺寸 A 4	PART NO. 料號 C0110-XXSAEB00R
DATE 制表日 2012/07/28	PAGE 張數 1 OF 1	REV. 版次 A	