



Technical Data

Material:

Pin(outer sleeve):Brass,machined CuZn38Pb2

Plating(outer sleeve):

Tin Plated:2μm/80μ"NI, 5μm/200μ"Sn

Gold Plated:2μm"/80μ"Ni, 0.8μ" gold

Insuiator:PPS UL94V-0

Electrical:

Current rating:3Amps/contact max.

Contact resistance:≤4mΩ/contact

Insuiation resistance:≥1000MΩ at V=100V

Dleictric Withstanding Voltage:1000V AV Min

Operaling voitage:60VAC/DC

Mechanical:

Operaling temperature:-40° C to+105° C

Soldering temperature:+255° C

Critical Dimensions:⊛

RoHS Compliant		HSM 玄茂科技股份有限公司	
		HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 HELEN	SCALE 比例 参考	TOLERANCE X.XXX ±0.05 X.XX ±0.15 X.X ±0.20 X. ±0.30 ANGLE ±5.0°	PART NAME 品名 2.54mm SIP SOCKET MACHINED PIN STRAIGHT PIN H=3.0mm DUAL ROW 2XXXPIN PIN LENGTH:3.5+3.0+3.5=10.0mm GOLD FLASH PLATING BLACK COLOR ROHS
DWG. 製圖 ABBY		UNIT 單位 MM	SIZE. 紙張尺寸 A4
DATE 制表日 2019/10/03	PAGE 張數 1 OF 1	REV. 版次 A	PART NO. 料號 C0122-XXDNGBA0R