



RECOMMENDED  
CABLE STRIPPING DIM'S

DIMENSIONS ARE IN MILLIMETERS	
UNLESS OTHERWISE SPECIFIED TOLERANCES	
0.5-5	±0.2
5-30	±0.4
30-120	±0.6
120-315	±1
315-1000	±1.6
1000-2000	±2.4

12	NUT	ZINC	1	NICKEL PLATED
11	WASHER	IRON	1	NICKEL PLATED
10	GASKET	RUBBER	1	RED
9	WASHER	ZINC	1	NICKEL PLATED
8	CENTER CONTACT	BRASS	1	GOLD PLATED
7	BODY	ZINC	1	NICKEL PLATED
6	WASHER	ZINC	1	NICKEL PLATED
5	SPRING	65Mn	1	NATURAL
4	OUT CONTACT	ZINC	1	NICKEL PLATED
3	GASKET	PVC	1	RED
2	SHELL	ZINC	1	NICKEL PLATED
1	INSULATOR	POM	1	NATURAL
ITEM	DESCRIPTION	MATERIAL	Q'TY	FINISHED

RoHS  
Compliant

**HSM** 玄茂科技股份有限公司  
**HSUAN MAO TECHNOLOGY CO., LTD.**

APPD.  
核准  
Betty  
DATE 制表日  
2019/09/18

SCALE  
比例 参考  
UNIT  
單位 M M  
PAGE  
張數 1 OF 1

PART NAME 品名  
BNC MALE CLAMP 180° FOR RG59U 50Ω  
CENTER CONTACT: BRASS, GOLD  
PLATED SHELL: ZINC, NICKEL PLATED  
ROHS  
PART NO.  
料號 C0409-SCAAM000R