



● MATERIALS:

Housing: Plastic Thermoplastic
P.B.T UL94V-0 Black
Contacts: Phosphor Bronze Gold
Selective Plated
Front Shell: Steel Nickel Plated Over Copper

● ELECTRICAL CHARACTERISTICS:

Contact Current Rating: 0.5 Amp
Dielectric Withstanding Voltage: 500V AC
Insulation Resistance: >500MΩ/Min
Contact Resistance: 35mΩ/Max
Operation Temperature: -55°C ~ +85°C

● MATERIALS: (RoHS Compliant)

Back Shell: Zinc Alloy Nickel Plated Over Copper
Flat Screws: Steel Nickel Plated Over Copper
Cable Clipper: Steel Nickel Plated Over Copper
Spring Latches: Stainless Steel

| | | | |
|----------------|------------|--|---|
| RoHS Compliant | | HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD. | |
| APPD. 核准 | | TOLERANCE 容許公差 | PART NAME 品名 |
| DWG. 製圖 | Betty | SCALE 比例 參考 | 1.27mm SCSI II CEN. SOLDER CONNECTOR 26P MALE SPRING LATCHES(STAINLESS STEEL) METAL HOOD(ZINC PLATED NICKEL OVER COPPER) ENTRY HOLE SIZE:φ8mm HP CEN. 26P MALE SOLDER ASSEMBLY ROHS |
| DATE 制表日 | 2016/07/13 | UNIT 單位 M M | PART NO. |
| | | PAGE 張數 1 OF 1 | C0515-26MELXZ0R |
| | | REV. 版次 C | 料號 |