



NOTE
 MATERIAL
 INSULATOR: PBT +30%GF
 CONTACTS: BRASS
 SHELL: SPCD
 CONTACT PLATING: GOLD PLATING OVER NICKEL
 ELECTRICAL SPECIFICATION
 CURRENT RATING: 3A;
 VOLTAGE RATING: 250V AC
 CONTACT RESISTANCE: 25mΩ MAX.
 INSULATION RESISTANCE: 1000MΩ MIN 500V DC.
 DIELECTRIC WITHSTANDING VOLTAGE: 1000V AC
 ENVIRONMENTAL
 OPERATING TEMPERATURE: -55°C~105°C.

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 HELEN		TOLERANCE XX ±0.30 XX' ±3' XXX ±0.15 XXX' ±1' XXXX ±0.10 XXXX' ±0.5'	PART NAME 品名 D-SUB H.D. PCB RIGHT ANGLE FOR NOTEBOOK DIP TYPE 15P FEMALE 3 CONTACTS ROW 4-40 THREAD RIVET W/BOARDLOCK FIX SCREWS(4.8X11.8) TIN SHELL SELECTIVE GOLD ROHS
DWG. 製圖 ABBY	SCALE 比例 參考	UNIT 單位 MM	PART NO. 料號 C0523-15FBCTSXR
DATE 制表日 2011/07/29	PAGE 張數 1 OF 1	SIZE 紙張尺寸 A4	REV. 版本 A