



P.C.B LAYOUT

MATERIALS AND FINISH

SHELL : STEEL MATERIAL, FRONT SHEEL NICKEL FINISHED
 BACK SHEEL TIN FINISHED
 INSULATOR : PA9T THERMOPLASTIC, 30% GLASS
 FILLED, UL 94V-0 RATED, BLACK COLOR
 CONTACT MATERIAL: BRASS
 CONTACT FINISH : G/F
 RIVETED INSERT : BRASS MATERIAL , NICKEL FINISHED

ELECTRICAL CHARACTERISTICS

CONTACT CURRENT RATING : 5.0 AMPS
 CONTACT RESISTANCE : 30 MILLIOHMS MAX.
 DIELECTRIC WITHSTANDING VOLTAGE : 1000 V AC MIN.
 INSULATION RESISTANCE : 5000 MEGAOHMS MIN.
 TEMPERATURE RATING : -55°C ~ +105°C

| | | | |
|-----------------------|------------|---------------------------------------|--|
| RoHS Compliant | | HSM 玄茂科技股份有限公司 | |
| | | HSUAN MAO TECHNOLOGY CO., LTD. | |
| APPD. 核准 | | TOLERANCE 容許公差 | PART NAME 品名 |
| DWG. 製圖 | Hedy | SCALE 比例 參考 | D-SUB PCB STRAIGHT DIP TYPE FOR NOOTBOOK 9P MALE |
| DATE 制表日 | 2016/11/22 | UNIT 單位 | THREAD RIVET NON ACCESSORIES |
| | | PAGE 張數 | NICKEL SHELL+DIMPLE GOLD PLATING |
| | | | BLACK INSULATOR(MACHINED PIN)ROHS |
| | | | PART NO. |
| | | | 料號 C0525-09MAABGBR |