



NOTE
 MATERIAL
 INSULATOR: PBT,UL 94V-0 RATED
 CONTACTS: BRASS
 SHELL: COLD ROLLER STEEL
 SCREW:BRASS PLATED NICKEL
 CONTACT PLATING: GOLD PLATING OVER NICKEL
 ELECTRICAL SPECIFICATION
 CURRENT RATING: 3AMP;
 CONTACT RESISTANCE: 25mΩ MAX.
 INSULATION RESISTANCE:5000MΩ MIN 500V DC.
 DIELECTRIC WITHSTANDING VOLTAGE:1000V AC
 ENVIRONMENTAL
 OPERRRATING TEMPERATURE: -55°C~105°C.

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准		TOLERANCE X. ±0.38 XX' ±1' XX ±0.35 XXX' ±0.05' XXX ±0.25 XXXX ±0.10	PART NAME 品名 D-SUB R/A FOR NOTE BOOK 9PIN FEMALE ADD SCREWS 4.8*11.8mm NICKEL SHELL SELECTIVE GOLD PLATING BLACK COLOR (DUAL ROWS) ROHS
DWG. 製圖 Betty		SCALE 比例 參考	SIZE. 紙張尺寸 A 4
DATE 製表日 2017/04/11	UNIT 單位 MM	PAGE 張數 1 OF 1	REV. 版次 A