



SPECIFICATIONS

1. D-SUB
- 1.1 Voltage: 250 VAC(RMS) Max.
- 1.2 Current Rating: 3 Ampere per Contact
- 1.3 Contact Resistance: 25 Milliohms Max.
- 1.4 Insulation Resistance: 1000 Megohms Min.
- 1.5 Dielectric Withstanding Voltage: 500 VAC(RMS)
- 1.6 Total Mating Force: 9.4 Kgf Max.
- 1.7 Total Unmating Force: 1.4 Kgf Min.
- 1.8 Operating Temperature: -55°C to +85°C

NOTES

1. MATERIAL:
 - Housing: PBT, UL 94V-0, Black.
 - Terminal: Copper Alloy.
 - Shell: SPCC.
 - Boardlock: Copper Alloy.
 - Rivet: Copper Alloy.
2. FINISH:
 - Terminal: Gold Plated On Contact Area.
Tin Plated On Solder Area.
 - Shell: Nickel Plated.
 - Boardlock: Tin Plated.
 - Rivet: Nickel Plated.
3. This Product is LEAD-FREE & RoHS Compliance Product.

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 HELEN	SCALE 比例 參考	TOLERANCE 容許公差 XX ±0.25 XXX ±0.13 .X" ±2"	PART NAME 品名 D-SUB R/A FOR NOTE BOOK XXP FEMALE FIX SCREWS 4.8*11.8mm NICKEL SHELL BLACK COLOR (DUAL ROWS) ROHS
DWG. 製圖 ABBY	UNIT 單位 MM	SIZE. 紙張尺寸 A4	PART NO. 料號 C0528-25FBCNXBR
DATE 制表日 2018/08/17	PAGE 張數 1 OF 1	REV. 版次 A	