



P.C.B. PLYOUT

一、 MATERIAL:

1. Insulator: PBT+30%Glass Fiber (UL94V-0)
2. Contact: Brass
3. Contact Plated: Gold Flash over Tin Or Glod Plated Or Tin Plated
4. Shell: Steel, Nickel Plated

二、 SPECIFICATION:

1. Current Rating: 5 AMPS
2. Insulation Resistance: 5000MΩ MIN. At 500VDC
3. Dielectric Strength: 500V for One minute
4. Operation Temperature: -55° C~+105° C.

PIN	A	B	C
9	16.30	24.99	30.80
15	24.60	33.30	39.20
25	38.30	47.04	53.10
37	54.80	63.50	69.34

RoHS Compliant		玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 Betty	SCALE 比例 参考	TOLERANCE .0±0.30 .00±0.25 .000±0.05 0±1.0° .00±0.5° .000±0.1°	PART NAME 品名 D-SUB PCB RIGHT ANGLE 7.2mm STAMPED PIN XXP FEMALE FIX BOARDLOCK WITH 4.8x11.8mm SCREWS NICKEL SHELL ROHS
DWG. 製圖 Betty	UNIT 單位 MM	SIZE 紙張尺寸 A 4	PART NO. 料號 C0550-XXFACNXXR
DATE 制表日 2012/08/09	PAGE 張數 1 OF 1	REV. 版次 A	