



- 一、 MATERIAL:
1. Insulator: PBT+30%Glass Fiber (UL94V-0)
  2. Contact: Brass
  3. Contact Plated: Gold Flash over Tin
  4. Shell: Steel, Nickel Plated
- 二、 SPECIFICATION:
1. Current Rating: 5 AMPS
  2. Insulation Resistance: 1000M Ω MIN. At 500VDC
  3. Dielectric Strength: 500V for One minute
  4. Operation Temperature: -55 °C~+105 °C.

RECOMMENDED P.C.B LAYOUT  
INSPECTION DIMENSION:(A)~(L)

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准	SCALE 比例	TOLERANCE 容許公差	PART NAME 品名
DWG. 製圖	UNIT 單位	SCALE .0 ± 0.30 .00 ± 0.20 ANG. ± 3°	D-SUB RIGHT ANGLE DUAL PORTS DB25F/DB9M+HDD15F DUAL BOARDLOCK(CENTER LINE 8.18mm) NON ACCESSORIES PORT SPACING 19.05mm SELECTIVE GOLD PLATING BLACK INSULATOR ROHS
DATE 制表日	PAGE 張數	SIZE 紙張尺寸	PART NO. 料號
2014/12/09	1 OF 1	A 4	C0553-07INABSBR
Betty	REV. 版次	A	