



MATERIAL:
 Insulator: Glass-Filled Thermoplastic
 PBT, UL94V-0 rated
 Contact: Brass
 Shell: Steel, refer to ordering information for plating
 Clinch Nut: Brass, 100U" Min Nickel Plated
 Screwlock: Brass, 100U" Min Nickel Plated

Electrical
 Contact Resistance: 20milliohms Max at 1AMP DC.
 Insulation Resistance: 1000magohms at 500V DC
 Dielectric Withstanding Voltage: 1000V AC/rms 60Hz for 1 minute
 Current Rating: 3 AMP
 Voltage Rating: 250V AC/rms 60Hz

M/F DIM	A	B	C	D	E	F	G	H	I	J
15P	16.30	25.00	30.80	7.90	12.50	7.039	2.286	1.981	10.70	19.30
26P	24.70	33.30	39.10	7.90	12.50	6.871	2.286	1.981	10.70	27.50
44P	38.40	47.00	53.00	7.90	12.50	6.863	2.286	1.981	10.70	41.30
62P	54.80	63.50	69.30	7.90	12.50	6.998	2.413	1.981	10.70	57.70

**RoHS
Compliant**

**HSM 玄茂科技股份有限公司
Hsuan Mao Technology CO., LTD.**

APPD.		TOLERANCE	PART NAME 品名
DWG. Karen	SCALE 参考	.0 ± .00 ± ANG. ±	H. D. D-SUB PCB STRAIGHT STAMPED PIN FEMALE THROUGH HOLE ROHS LOW-LEAD
DATE 2012/09/12	UNIT M M	SIZE A 4	PART NO. C0561-XXFAAXXR
	PAGE 1 OF 1	REV. B	料 號