

Label: orange color with white character

One side: SERIAL PORT ADAPTORS D9/D25

The other side: MINI ADAPTER

SPECIFICATION

INSULATOR: PBT Glass fibre reinforced UL 94 VO(black)

CONTACT: Brass

CONTACT PLATING: Gold plated over nickel

SHELL: Tin plated shell

MA 001A (DB9M/25F ADAPTOR)

PIN OUT: 09Male


25Female

| | | |
|---|-------|----|
| 1 | ----- | 8 |
| 2 | ----- | 3 |
| 3 | ----- | 2 |
| 4 | ----- | 20 |
| 5 | ----- | 7 |
| 6 | ----- | 6 |
| 7 | ----- | 4 |
| 8 | ----- | 5 |
| 9 | ----- | 22 |
| G | ----- | G |

RoHS
Compliant

HSM 玄茂科技股份有限公司
HSUAN MAO TECHNOLOGY CO., LTD.

APPD.
核准 BETTY



UNLESS OTHER-WISE
SPECIFIED TOLERANCE:
0.0: ±0.20
0.00: ±0.15
0.000: ±0.05

PART NAME 品名
D-SUB GENDER CHANGER MINI TYPE 9P MALE/25P FEMALE
WITH YELLOW LABEL FLASH GOLD PLATING
BLACK INSULATOR ROHS

DWG.
製圖 BETTY

SCALE
比例 參考

UNIT
單位 MM

PART NO.

DATE 制表日
2011/01/18

PAGE
張數 1 OF 1

REV.
版次 A

料號 C0564-03BAYGB0R