



#4-40

2 Pcs

**MATERIALS AND FINISH**  
 SHELL : STEEL MATERIAL, FRONT SHELL TIN FINISHED  
 BACK SHELL TIN FINISHED  
 DIMPLES ON PLUG ONLY  
 INSULATOR : PBT THERMOPLASTIC, 30% GLASS FILLED,  
 UL 94V-0 RATED, BLACK COLOR  
 COAXIAL CONTACT : COPPER ALLOY, FULL GOLD FLASH

**ELECTRICAL CHARACTERISTICS**  
 COAXIAL CONTACT IMPEDANCE : 50Ω  
 COAXIAL CONTACT RESISTANCE : 2.7 mΩ MAX.  
 INSULATION RESISTANCE : 10<sup>7</sup>mΩ MIN.  
 TEMPERATURE RATING : -55°C ~ +125°C

Tolerance ± 0.30

RoHS Compliant		<b>HSM</b> 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 BETTY	TOLERANCE 容許公差 0 ± .00 ± ANG ±	PART NAME 品名 D-SUB COAXIAL SOLDER TYPE 2W2 FEMALE 50 OHMS THROUGH HOLE TIN SHELL WITH SIGNAL CONTACT GOLD PLATING BLACK INSULATOR ROHS	
DWG. 製圖 KAREN		SCALE 比例 參考	UNIT 單位 MM
DATE 制表日 2012/07/27	PAGE 張數 1 OF 1	SIZE 紙張尺寸 A4	REV. 版本 A
		PART NO. 料號 C0590-KFAAT0GBR	