



	A±0.2	B±0.2	C±0.2	D±0.03	E±0.2
14P	43.92	35.99	25.2	12.25	11.9
24P	54.71	46.79	36.0	12.25	11.9
36P	67.69	59.74	48.9	12.25	11.9
50P	82.78	74.85	64.0	12.25	11.9

ELECTRICAL CHARACTERISTICS:

CONTACT CURRENT RATING: 1 AMPERES.
 DIELECTRIC WITHSTANDING VOLTAGE: AC 500V R.M.S
 INSULATION RESISTANCE: 500 MEGOHMS MINIMUM AT DC 500V.
 CONTACT RESISTANCE: 30 MILLIOHMS MAXIMUM.
 OPERATING TEMPERATURE: -55C TO 105C.

MATERIALS:

CONTACT: BRASS.
 INSULATOR: P.B.T. UL 94-V0 RATED.
 SHELL: COLD ROLLED STEEL.

FINISHES:

CONTACTS: GOLD PLATED OR SELECTIVE GOLD.
 SHELL: NICKEL PLATED.

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 Ivy	SCALE 比例 参考	TOLERANCE 容許公差 .0 ± .00 ± ANG. ±	PART NAME 品名 CENTRONIC SOLDER TYPE XXF PANEL TYPE W/O LATCH NICKEL THROUGH HOLE ROHS LOW-LEAD
DWG. 製圖 Yumi	UNIT 單位 MM	SIZE 紙張尺寸 A4	PART NO. 料號 C0710-XXFAAXX0R
DATE 制表日 2010/11/25	PAGE 張數 1 OF 1	REV. 版次 A	