



ELECTRICAL CHARACTERISTICS:

CONTACT CURRENT RATING: 1 AMPERES.
 DIELECTRIC WITHSTANDING VOLTAGE: AC 500V R.M.S
 INSULATION RESISTANCE: 500 MEGOHMS MINIMUM AT DC 500V.
 CONTACT RESISTANCE: 30 MILLIOHMS MAXIMUM.
 OPERATING TEMPERATURE: -55C TO 105C.

MATERIALS:

CONTACT: BRASS..
 INSULATOR: P.B.T. UL 94-V0 RATED.
 SHELL: COLD ROLLED STEEL..
 HOOD: COLD ROLLED STEEL.

FINISHES:

CONTACTS: GOLD PLATED 3u" ,5u" ,10u" ,15u" ,30u" .
 SHELL: NICKEL PLATED.

PART NO.	A±0.2	B±0.2	C±0.2	D±0.03	E±0.2	F±0.2
14	43.92	35.99	25.2	15.25	11.9	29.0
24	54.71	46.79	36.0	15.25	11.9	39.8
36	67.69	59.74	48.9	15.25	11.9	53.0
50	82.78	74.85	64.0	15.25	11.9	68.1

RoHS
Compliant

HSM 玄茂科技股份有限公司
HSUAN MAO TECHNOLOGY CO., LTD.

APPD. 核准 HELEN	SCALE 比例 参考	TOLERANCE 容許公差 .0 ± 0.25 .00 ± ANG. ±	PART NAME 品名 CENTRONIC SOLDER TYPE XXP FEMALE W/REAR METAL COVER W/MOUNTING CLIP RIVET TYPE W/LATCH NICKEL SHELL BULE INSULATOR ROHS
DWG. 製圖 ABBY	UNIT 單位 MM	SIZE 紙張尺寸 A4	PART NO. 料號 C0710-XXFEAXLYR
DATE 制表日 2017/06/16	PAGE 張數 1 OF 1	REV. 版本 A	