



PIN	A±0.2	B±0.2	C±0.2	D±0.03	E±0.2
14P	38.8	25.6	15.2	12.25	1.15
24P	49.3	36.47	15.2	12.25	1.15
36P	62.0	49.35	15.2	12.25	1.15
50P	77.4	64.47	15.2	12.25	1.15

ELECTRICAL CHARACTERISTICS:
 CONTACT CURRENT RATING: 1 AMPERES.
 DIELECTRIC WITHSTANDING VOLTAGE: AC 500V R.M.S
 INSULATION RESISTANCE: 500 MEGOHMS MINIMUM AT DC 500V.
 CONTACT RESISTANCE: 30 MILLIOHMS MAXIMUM.
 OPERATING TEMPERATURE: -55C TO 105C.

MECHANICAL CHARACTERISTICS:
 CONTACT INSERTION FORCE: 2.5 KG MAXIMUM.
 CONTACT SEPARATION FORCE: 2.0 KG MINIMUM.

MATERIALS:
 CONTACT: BRASS.
 INSULATOR: P.B.T. UL 94-V0 RATED.(D202G30)
 SHELL: COLD ROLLED STEEL.(JIS G3141)

FINISHES:
 CONTACTS:GOLD PLATED.
 SHELL:NICKEL OR TIN PLATED.

Material:
 Hood: ABS UL 94HB
 Cable Clipper: NYLON 66 UL94V-2

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 Angel	SCALE 比例 参考	TOLERANCE 容許公差 .0 ± .00 ± ANG. ±	PART NAME 品名 CENTRONIC SOLDER TYPE XX M METAL COVER ROHS LOW-LEAD
DWG. 製圖 Yumi	UNIT 單位 M M	SIZE 紙張尺寸 A 4	PART NO. 料號 C0710-XXMPOXX0R
DATE 制表日 2008/12/31	PAGE 張數 1 OF 1	REV. 版次 A	