



ELECTRICAL CHARACTERISTICS:

CONTACT CURRENT RATING: 1 AMPERES.
 DIELECTRIC WITHSTANDING VOLTAGE: AC 500V R.M.S
 INSULATION RESISTANCE: 500 MEGOHMS MINIMUM AT DC 500V.
 CONTACT RESISTANCE: 30 MILLIOHMS MAXIMUM.
 OPERATING TEMPERATURE: -55C TO 105C.

MATERIALS:

CONTACT: BRASS..
 INSULATOR: P.B.T. UL 94-V0 RATED.
 SHELL: COLD ROLLED STEEL.
 HOOD: POLYPROPYLENE.

FINISHES:

CONTACTS: GOLD PLATED 3u" ,5u" ,10u" ,15u" ,30u" .
 SHELL: NICKEL PLATED.

PART NO.	A±0.2	B±0.2	C±0.2	D±0.03	E±0.2
14S	43.92	35.99	25.2	12.25	11.9
24S	54.71	46.79	36.0	12.25	11.9
36S	67.69	59.74	48.9	12.25	11.9
50S	82.78	74.85	64.0	12.25	11.9

RoHS Compliant **HSM 玄茂科技股份有限公司**
HSUAN MAO TECHNOLOGY CO., LTD.

APPD. 核准 BETTY		TOLERANCE 容許公差	PART NAME 品名
DWG. 製圖 KAREN		SCALE 比例 參考	
DATE 制表日 2015/02/10	UNIT 單位 MM	SIZE 板張尺寸 A4	PART NO.
PAGE 張數 1 OF 1	REV. 版本 B		料號 C0712-XXFAAXL0R