


P.C.B. LAYOUT



ELECTRICAL CHARACTERISTICS:

CONTACT CURRENT RATING: 1 AMPERES.
 DIELECTRIC WITHSTANDING VOLTAGE: AC 500V R.M.S
 INSULATION RESISTANCE: 500 MEGOHMS MINIMUM AT DC 500V.
 CONTACT RESISTANCE: 30 MILLIOHMS MAXIMUM.
 OPERATING TEMPERATURE: -55C TO 105C.

MECHANICAL CHARACTERISTICS:

CONTACT INSERTION FORCE: 2.5 KG MAXIMUM.
 CONTACT SEPARATION FORCE: 2.0 KG MINIMUM.

MATERIALS:

CONTACT: BRASS.
 INSULATOR: P.B.T. UL 94-V0 RATED.(D202G30)
 SHELL: COLD ROLLED STEEL.(JIS G3141)

FINISHES:

CONTACTS:GOLD PLATED.
 SHELL:NICKEL OR TIN PLATED.

PART NO.	A±0.2	B±0.2	C±0.2	D±0.03	E±0.2
14P	38.8	25.6	15.2	12.25	1.15
24P	49.3	36.47	15.2	12.25	1.15
36P	62.0	49.35	15.2	12.25	1.15
50P	77.4	64.47	15.2	12.25	1.15

RoHS
Compliant

HSM 玄茂科技股份有限公司
HSUAN MAO TECHNOLOGY CO., LTD.

APPD. 核准 HELEN
 DWG. 製圖 ABBY
 DATE 制表日 2015/11/03

SCALE 比例 參考
 UNIT 單位 MM
 PAGE 張數 1 OF 1

TOLERANCE 容許公差
 0 ± 0.3
 .00 ± 0.2
 ANG. ±
 SIZE. 紙張尺寸 A4
 REV. 版本 B

PART NAME 品名
 CENTRONIC PCB STRAIGHT XXM
 W/NOTCH EAR W/O LATCH NICKEL
 SHELL BLUEK COLOR ROHS

PART NO. C0712-XXMC0SL0R
 料號