



ELECTRICAL CHARACTERISTICS:
 CONTACT CURRENT RATING: 1 AMPERES.
 DIELECTRIC WITHSTANDING VOLTAGE: AC 500V R.M.S
 INSULATION RESISTANCE: 500 MEGOHMS MINIMUM AT DC 500V.
 CONTACT RESISTANCE: 30 MILLIOHMS MAXIMUM.
 OPERATING TEMPERATURE: -55C TO 105C.

MATERIALS:
 CONTACT: BRASS..
 INSULATOR: P.B.T. UL 94-V0 RATED.
 SHELL: COLD ROLLED STEEL.

FINISHES:
 CONTACTS: SELECTIVE GOLD PLATED
 SHELL: NICKEL PLATED.

P.C.B. LAYOUT

| PART NO. | A±0.2 | B±0.2 | C±0.2 | D±0.2 | E±0.3 |
|----------|-------|-------|-------|-------|-------|
| 36 | 67.69 | 59.74 | 48.9 | 15.5 | 11.9 |
| 50 | 82.78 | 74.85 | 64.0 | 15.5 | 11.9 |

| | | | |
|-----------------------|-------------------|--|--|
| RoHS Compliant | | HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD. | |
| APPD. 核准 | | TOLERANCE 容許公差 | PART NAME 品名 CENTRONIC PCB RIGHT ANGLE TYPE 36P OR 50P FEMALE RIVET WITH L-SHAPE WITH LATCH SELECTIVE GOLD PLATING BLUE COLOR WITH MOUNTING CLIP RIVET ROHS |
| DWG. 製圖 | <i>Helen</i> | SCALE 比例 參考 | SIZE. 紙張尺寸 A4 |
| DATE 制表日 2017/12/1 | UNIT 單位 MM | REV. 版本 B | PART NO. 料號 C0713-XXFBDSLRY |
| | PAGE 張數 1 OF 1 | | |