



NOTES 1:
 UL Standard :
 1. Rating: 300V 15A
 2. Insulation Withstands Voltage:
 AC 2000V at 1 minute
 3. Using Temperature Range:
 -40°C~+115°C
 IEC Standard :
 1. Rating: 600V 18A
 2. Rate Impulse Voltage: 4000V
 3. Insulation Resistance:
 500MΩ or more at DC500V
 4. Material Group : I
 5. Pollution Degree : 2
 6. Overvoltage Category: II
 7. Using Temperature Range:
 -40°C~+110°C

P	4	6	8	10	12	14	16	18	20	22	24	26
U	5.00	10.00	15.00	20.00	25.00	30.00	35.00	40.00	45.00	50.00	55.00	60.00
V	22.00	27.00	32.00	37.00	42.00	47.00	52.00	57.00	62.00	67.00	72.00	77.00
P	28	30	32	34	36							
U	65.00	70.00	75.00	80.00	85.00							
V	82.00	87.00	92.00	97.00	102.00							

5	NUT	COPPER ALLOY	M2.5x0.45
4	SOLDER PIN	COPPER ALLOY	Tin Plated
3	SOLDER PIN	COPPER ALLOY	Tin Plated
2	COVER	PA66	UL94-V0 GREEN
1	HOUSING	PA66	UL94-V0 GREEN
ITEM	NAME OF PART	MATERIAL	NOTES

Total Pitch Tolerances		Normal Dimension Tolerances	
0~30	±0.20	0~30	±0.25
over 30~53	±0.25	over 30~53	±0.30
over 53~70	±0.30	over 53~70	±0.35
over 70~90	±0.35	over 70~90	±0.44
over 90~115	±0.44	over 90~115	±0.55
over 115~150	±0.55	over 115~150	±0.70
over 150~200	±0.70	over 150~200	±0.85
over 200~250	±0.85	over 200~250	±1.00
over 250~320	±1.00	over 250~320	±1.20

RoHS Compliant

HSM 玄茂科技股份有限公司
HSUAN MAO TECHNOLOGY CO., LTD.

APPD. 核准	Betty	SCALE 比例 参考	TOLERANCE 容許公差 0 ± .00 ± ANG. ±	PART NAME 品名 5.0MM HEADER FOR PLUGGABLE TERMINAL BLOCKS DOUBLE-DECKED H=22.0MM 2XXXPIN 90° WITH SCREW HOLE TIN PLATING GREEN INSULATOR ROHS
DWG. 製圖	DATE 制表日	UNIT 單位	SIZE 紙張尺寸	PART NO. 料號
	2021/07/14	M M	A 4	C0917-XXRYTE00R
		PAGE 張數	REV. 版次	
		1 OF 1	A	