



	P2	3	4	5	6	7	8	9	10	11	12
U	3.81	7.62	11.43	15.24	19.05	22.86	26.67	30.48	34.29	38.1	41.91

	P13	14	15	16	17	18	19	20	21	22	23	24
U	45.72	49.53	53.34	57.15	60.96	64.77	68.58	72.39	76.2	80.01	83.82	87.63

NOTES:

1. Rating: 300V 8 A
PITCH: 3.81 mm
2. Insulation Withstands Voltage:
AC 2500V at 1 minute
3. Insulation Resistance:
500MΩ or more at DC500V
4. Using Temperature Range:
-40°C~+105°C
5. Screw Torque Value: 2.9 kgf-cm
6. Suitable Electric Wire: AWG 16~30
Strip length: 6~7mm
7. RoHS Compliance

Normal Geometric Tolerancing				
—	//	≡	⊥	
0 to 100	±0.2	0.3	0 to 10	±0.2
over 100 to 150	±0.3		over 10	±0.3
over 150	±0.5			
Total Pitch Tolerances		Normal dimension Tolerances		
0<U≤30	±0.20	0~30	±0.25	
30<U≤53	±0.25	over 30~53	±0.30	
53<U≤70	±0.30	over 53~70	±0.35	
70<U≤90	±0.35	over 70~90	±0.44	
90<U≤115	±0.44	over 90~115	±0.55	
115<U≤150	±0.55	over 115~150	±0.70	

ITEM	NAME OF PART	MATERIAL	NOTES
6	COVER	PA66	UL94-V0 GREEN
5	SOLDER PIN	COPPER-ALLOY	Tin Plated
4	WIRE CAGE	STEEL	Zn Plated
3	CLAMP	SPCC	Zn Plated
2	SCREW	STEEL	Zn Plated
1	HOUSING	PA66	UL94-V0 GREEN

RoHS Compliant

HSM 玄茂科技股份有限公司
HSUAN MAO TECHNOLOGY CO., LTD.

APPD. 核准 Betty
DWG. 製圖 Karen
DATE 制表日 2012/03/09

TOLERANCE 容許公差
SCALE 比例 參考
UNIT 單位 MM
PAGE 張數 1 OF 1
REV. 版本 A

PART NAME 品名
3.81mm TERMINAL BLOCK WIRE CAGE TYPE
XXP SUITABLE FOR 16~30AWG NICKEL PLATED
WITHOUT EAR(W/O SCREW HOLE) GREEN
COLOR ROHS
PART NO. 料號 C0925-XXN8NE00R