



SPECIFICATIONS

- ① Housing Material: Phenolic , Black
- ② Screw: M3.5 Nickel Plated Steel
- ③ Terminals: Tin Plated Brass

Screws Torque: 12 In-Lb

Wire Range: 12~18 WG

Rated: 20 Amperes.AC250V

Operation Temperature: -40°C~+160°C

Insulation withstands volt: AC2000V min

Insulation resistance: >1000MΩ or more at DC500V

POLE	2	3	4	5	6	7	8	9	10	11	12	13	14	15
A	41.5	52.5	63.5	74.5	85.5	96.5	107.5	118.5	129.5	140.25	151.5	162.5	173.5	184.5
B	33	44	55	66	77	88	99	110	121	132	143	154	165	176
POLE	16	17	18	19	20	21	22	23	24	25	26			
A	195.5	206.5	217.5	228.5	239.5	250.5	261.5	272.5	283.5	294.5	305.5			
B	187	198	209	220	231	242	253	264	275	286	297			

POLES	A	B
02P~06P	±0.8	±0.7
07P~12P	±0.9	±0.8
13P~18P	±1.00	±0.9
19P~24P	±1.10	±1.00
25P~30P	±1.20	±1.10

RoHS
Compliant

HSM 玄茂科技股份有限公司
HSUAN MAO TECHNOLOGY CO., LTD.

APPD. 核准 HELEN		TOLERANCE 容許公差 .0 ± .00 ± ANG. ±	PART NAME 品名 11mm DOUBLE ROW PHENOLIC TYPE TERMINAL BLOCK H=13.25mm 2XXXP SUITABLE FOR 12~18AWG TIN PLATING BLACK INSULATOR ROHS
DWG. 製圖 ABBY	SCALE 比例 參考	UNIT 單位 MM	
DATE 制表日 2019/05/24	PAGE 張數 1 OF 1	REV. 版次 A	
			PART NO. 料號 C0931-XXBMTB00R