



MATERIAL

Contact Pin : Brass
Green Product High Temp

SPECIFICATION

Current Rate : 1 AMP
Insulation Resistance : 5000MΩMin. at DC 500V
Contact Resistance : 20mΩMax. at DC 100mA
Dielectric Voltage : AC 500V for one minute

POLES	DIM E	POLES	DIM E
		26	31.75
2	1.27	27	33.02
3	2.54	28	34.29
4	3.81	29	35.56
5	5.08	30	36.83
6	6.35	31	38.10
7	7.62	32	39.37
8	8.89	33	40.64
9	10.16	34	41.91
10	11.43	35	43.18
11	12.70	36	44.45
12	13.97	37	45.72
13	15.24	38	46.99
14	16.51	39	48.26
15	17.78	40	49.53
16	19.05	41	50.80
17	20.32	42	52.07
18	21.59	43	53.34
19	22.86	44	54.61
20	24.13	45	55.88
21	25.40	46	57.15
22	26.67	47	58.42
23	27.94	48	59.69
24	29.21	49	60.96
25	30.48	50	62.23

C=2.85mm D=2.2mm E=1.0mm

<p>RoHS Compliant</p> <p>APPD. 核准</p> <p>DWG. 製圖 Helen</p> <p>DATE 制表日 2018/5/4</p>	<p>SCALE 比例 參考</p> <p>UNIT 單位 MM</p> <p>PAGE 張數 1 OF 1</p>	<p>TOLERANCE 容許公差</p> <p>0 ± 0.35</p> <p>.00 ± 0.25</p> <p>ANG. ± 3°</p> <p>SIZE 紙張尺寸 A4</p> <p>REV. 版本 A</p>	<p>HSM 玄茂科技股份有限公司</p> <p>HSUAN MAO TECHNOLOGY CO., LTD.</p>
			<p>PART NAME 品名</p> <p>1.27mm PIN HEADER SINGLE ROW 1X??P</p> <p>RIGHT ANGLE TYPE H:2.5mm</p> <p>(C=2.85mm D=2.2mm E=1.0mm) ROHS</p>
			<p>PART NO.</p> <p>料號 C1170-XXARXR0R</p>