

	1	2	3	4	5	6	7	8																																								
A	<table border="1"> <tr><td>CONTACTS</td><td>2X21</td></tr> <tr><td>2X2</td><td>2X22</td></tr> <tr><td>2X3</td><td>2X23</td></tr> <tr><td>2X4</td><td>2X24</td></tr> <tr><td>2X5</td><td>2X25</td></tr> <tr><td>2X6</td><td>2X26</td></tr> <tr><td>2X7</td><td>2X27</td></tr> <tr><td>2X8</td><td>2X28</td></tr> <tr><td>2X9</td><td>2X29</td></tr> <tr><td>2X10</td><td>2X30</td></tr> <tr><td>2X11</td><td>2X31</td></tr> <tr><td>2X12</td><td>2X32</td></tr> <tr><td>2X13</td><td>2X33</td></tr> <tr><td>2X14</td><td>2X34</td></tr> <tr><td>2X15</td><td>2X35</td></tr> <tr><td>2X16</td><td>2X36</td></tr> <tr><td>2X17</td><td>2X37</td></tr> <tr><td>2X18</td><td>2X38</td></tr> <tr><td>2X19</td><td>2X39</td></tr> <tr><td>2X20</td><td>2X40</td></tr> </table>		CONTACTS	2X21	2X2	2X22	2X3	2X23	2X4	2X24	2X5	2X25	2X6	2X26	2X7	2X27	2X8	2X28	2X9	2X29	2X10	2X30	2X11	2X31	2X12	2X32	2X13	2X33	2X14	2X34	2X15	2X35	2X16	2X36	2X17	2X37	2X18	2X38	2X19	2X39	2X20	2X40						
CONTACTS	2X21																																															
2X2	2X22																																															
2X3	2X23																																															
2X4	2X24																																															
2X5	2X25																																															
2X6	2X26																																															
2X7	2X27																																															
2X8	2X28																																															
2X9	2X29																																															
2X10	2X30																																															
2X11	2X31																																															
2X12	2X32																																															
2X13	2X33																																															
2X14	2X34																																															
2X15	2X35																																															
2X16	2X36																																															
2X17	2X37																																															
2X18	2X38																																															
2X19	2X39																																															
2X20	2X40																																															
B				<p>CONTACTS/2x1.27</p> <p>3.40</p> <p>0.40 SQ</p>			<p>(CONTACTS/2-1)x1.27</p> <p>1.27</p> <p>∅0.65</p>																																									
C							RECOMMENDED P.C.B LAYOUT																																									
D				<p>(CONTACTS/2-1)x1.27</p> <p>1.27 BSC</p> <p>1.10</p>			<p>C: 3.0 mm D: 2.60 mm E: 1.2 mm</p>																																									
E																																																
F	<p>MATERIAL</p> <p>HOUSING : THERMOPLASTIC UL94V-0</p> <p>CONTACT : COPPER ALLOYS</p>																																															
G	<p>SPECIFICATION</p> <p>CURRENT: 1A</p> <p>OPERATING TEMPERATURE: -55°C TO +105°C</p> <p>CONTACT RESISTANCE : 20 MILLIOHMS MAX</p> <p>INSULATION RESISTANCE : 5000 MEGAOHMS MIN</p> <p>DIELECTRIC STRENGTH : 1000 VAC MIN</p> <p>DURABILITY : 100 CYCLES</p> <p>RETENTION FORCE : 700g MIN</p>																																															
H	<p>FINISH</p> <p>CONTACT PLATING SEE ORDER INFORMATION</p>					<p>RoHS Compliant</p> <p>APPD. 核准 Angel</p> <p>DWG. 製圖 Yumi</p> <p>DATE 制表日 2010/03/29</p>	<p>HSM 玄茂科技股份有限公司</p> <p>HSUAN MAO TECHNOLOGY CO., LTD.</p> <p>SCALE 比例 參考</p> <p>UNIT 單位 MM</p> <p>PAGE 張數 1 OF 1</p> <p>TOLERANCE .0=±0.38 .00=±0.25 ANG=±5°</p> <p>SIZE. 紙張尺寸 A4</p> <p>REV. 版次 A</p>	<p>PART NAME 品名</p> <p>1.27 X 1.27mm PIN HEADER DUALROW 2XXXP STRAIGHT TYPE H=1.1mm C=3.0 D=2.6 E=1.2mm ROHS</p> <p>PART NO. C1281-XXBRXAROR</p> <p>料號</p>																																								
	1	2	3	4	5	6	7	8																																								