



PN:C2804-XXBRGH00R

PN:C2804-XXARGH00R

SPECIFICATIONS

Material

Insulator : PBT, glass reinforced, rated UL 94V-0
 Contact : Phosphor Bronze

Electrical

Current Rating : 1 Amp
 Contact Resistance : 30 mΩ max.
 Insulation Resistance : 3000 MΩ min.
 Dielectric Withstanding Voltage : 500V AC for 1minute
 Operating Temperature : -40°C to +105°C

RECOMMENDED P.C.B LAYOUT

RECOMMENDED P.C.B LAYOUT

| | | | |
|----------------------------|---|---|--|
| <p>RoHS Compliant</p> | | <p>HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.</p> | |
| <p>APPD. 核准 HELEN</p> |  | <p>TOLERANCE 容許公差 .0 ± .00 ± ANG ±</p> | <p>PART NAME 品名 2.54mm FEMALE HEADER H:5.5mm DUAL ROW 2XXXP OR SINGLE ROW 1XXXP RIGHT ANGLE TYPE GOLD FLASH PLATING ROHS</p> |
| <p>DWG. 製圖 ABBY</p> | <p>SCALE 比例 參考</p> | <p>UNIT 單位 MM</p> | <p>PART NO. 料號 C2804-XXXRGH00R</p> |
| <p>DATE 制表日 2013/12/02</p> | <p>PAGE 張數 1 OF 1</p> | <p>REV. 版次 A</p> | |