



OPTION:
W/ LOCATING PEG OR W/O LOCATING PEG

SPECIFICATIONS

Material

Insulator : LCP, glass reinforced, rated UL 94V-0

Contact : Phosphor Bronze

Electrical

Current Rating : 1 Amp

Contact Resistance : 30 mΩ max.

Insulation Resistance : 3000 MΩ min.

Dielectric Withstanding Voltage : 500V AC for 1minute

Operating Temperature : -40°C to +105°C

C 2827 — 04 B D G H T 0

- | | | | |
|-------------------------------------|--|---------------------------------|--|
| 1. PRODUCTS:
C:Connector | 5. CONTACT TYPE:
D:S.M.T. | 7. INSULATOR HEIGHT:
H:6.4mm | 8. Packing OTHERS:
T:Tube Packing
R:Reel Packing
P:PAD+Tube Packing
Q:PAD+Reel Packing |
| 2. SERIES NO.:
2827 | 6. CONTACT PLATING:
T:Tin
S:Selective Gold
G:Gold Flash | | 9. BODY OPTION:
Y:W/ Locating Peg
O:W/O Locating Peg |
| 3. CONTACT NO.:
04(2x2)-80(2x40) | | | |
| 4. ROW TYPE:
B: Dual Rows | | | |

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准	SCALE 比例 参考	TOLERANCE 容許公差 .0 ± 0.25 .00 ± ANG. ±	PART NAME 品名 2.54mm FEMALE HEADER DUAL ROW H:6.4mm 2X??P SMT TYPE TOTAL HEIGHT=7.1mm ROHS
DWG. 製圖 HELEN	UNIT 單位 MM	SIZE 紙張尺寸 A4	PART NO. 料號 C2827-XXBDXHXXR
DATE 制表日 2010/11/9	PAGE 張數 1 OF 1	REV. 版本 A	