



**Specifications**

Current Rating: 3Amp

Insulation Resistance:  $1000M\Omega/\text{Min.}$

Dielectric Withstanding Voltage:  $600VAC$

Contact Resistance:  $20m\Omega/\text{Max.}$

Operating Temperature:  $-40^{\circ}C$  to  $+105^{\circ}C$

**Materials**

Contact Material: Phosphor Bronze

Insulator Material: High Temperature

Thermoplastic, UL 94V-0 Nylon 6T (Halogen Free)  
or the equivalent material

PIN 0.75X0.25

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准	Betty	SCALE 比例 参考	GENERAL TOLERANCE X: $\pm 5.0'$ X: $\pm 0.30$ .X: $\pm 3.0'$ X: $\pm 0.25$ .XX: $\pm 2.0'$ .XX: $\pm 0.15$ .XXX: $\pm 1.0'$ .XXX: $\pm 0.10$
DWG. 製圖		UNIT 單位 MM	SIZE. 紙張尺寸 A4
DATE 制表日		PAGE 張數 1 OF 1	REV. 版次 C
2017/03/10			PART NO. 料號 C2828-XXABXH0XR