



**Recommended
P.C. Board Hole Layout**

Specifications

- Current Rating : 3 Amps
- Insulator Resistance : 1000 Megohms min.
- Contact Resistance : 20 m ohms max.
- Dielectric Withstanding : AC 600V
- Operating Temperature : -40°C ~ +125°C
- Contact Material :Phosphor Bronze
- Insulator Material : Polyester, UL 94V-0 Nylon-9T
- Contact Plated : Standard:Full Gold Flash

RoHS Compliant		玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.						
APPD. 核准	 SCALE 比例 参考	GENERAL TOLERANCE	PART NAME 品名					
DWG. 製圖		<table border="1"> <tr> <td>X ± 0.50</td> <td>X' ± 5'</td> </tr> <tr> <td>.X ± 0.20</td> <td>.X' ± 2'</td> </tr> <tr> <td>.XX ± 0.10</td> <td>.XX' ± 1'</td> </tr> </table>	X ± 0.50	X' ± 5'	.X ± 0.20	.X' ± 2'	.XX ± 0.10	.XX' ± 1'
X ± 0.50	X' ± 5'							
.X ± 0.20	.X' ± 2'							
.XX ± 0.10	.XX' ± 1'							
DATE 制表日	UNIT 單位	SIZE. 紙張尺寸	PART NO.					
2020/02/04	M M	A 4	C2830-XXBSGHT1B					
	PAGE 張數	REV. 版次	料號					
	1 OF 1	A						