



SPECIFICATIONS

Current Rating: 3Amps
 Insulator Resistance: 5000Megohms min.
 Dielectric Withstanding: AC 500v
 Operating Temperature: -40°C ~ +105°C
 Contact Material: Brass
 Insulator Material: PBT
 Finish: Gold flash

Dimension List

Contacts Per row	Dimensions		Contacts Per row	Dimensions	
	A	B		A	B
1	2.54	0	21	53.34	50.80
2	5.08	2.54	22	55.88	53.34
3	7.62	5.08	23	58.42	55.88
4	10.16	7.62	24	60.96	58.42
5	12.70	10.16	25	63.50	60.96
6	15.24	12.70	26	66.04	63.50
7	17.78	15.24	27	68.58	66.04
8	20.32	17.78	28	68.58	68.58
9	22.86	20.32	29	71.12	68.58
10	25.40	22.86	30	73.66	71.12
11	27.94	25.40	31	76.20	73.66
12	30.48	27.94	32	78.74	76.20
13	33.02	30.48	33	81.28	78.74
14	35.56	33.02	34	83.82	81.28
15	38.10	35.56	35	86.36	83.82
16	40.64	38.10	36	88.90	86.36
17	43.18	40.64	37	91.44	88.90
18	45.72	43.18	38	93.98	91.44
19	48.26	45.72	39	96.52	93.98
20	50.80	48.26	40	101.6	96.52

RoHS Compliant **HSM** 玄茂科技股份有限公司
HSUAN MAO TECHNOLOGY CO., LTD.

APPD. 核准	<p>SCALE 比例 參考</p> <p>UNIT 單位 M M</p> <p>PAGE 張數 1 OF 1</p>	TOLERANCE 容許公差	PART NAME 品名
DWG. 製圖 Betty		.0 ± 0.30 .00 ± 0.20 ANG. ± 3°	2.54mm FEMALE HEADER SINGLE ROW H:3.55mm(W:2.5mm) 1XXXPIN STRAIGHT TYPE GOLD FLASH PLATING MATERIAL:PBT ROHS
DATE 制表日 2019/11/08		SIZE 紙張尺寸 A 4	PART NO. 料號 C2835-XXASGHP0R