



MATERIALS:
 INSULATOR: P.B.T. 30% GLASS FIBER, UL94V-0
 CONTACT MATERIAL: BRASS, GOLD FLASH OVER NICKEL

ELECTRICAL:
 CURRENT RATING: 1AMP DC
 INSULATION RESISTANCE: 5000MΩ MIN.
 CONTACT RESISTANCE: 30mΩ MAX.
 DIELECTRIC WITHSTANDING: 1000V AC
 OPERATING TEMPERATURE: -40°C ~ +105°C
 TERMINATED WITH 1.27mm PITCH FLAT RIBBON CABLE.

CONTACTS	A	B
08P	15.45	07.62
10P	17.95	10.16
14P	23.05	15.24
16P	25.50	17.78
18P	28.12	20.32
20P	30.68	22.86
24P	35.80	27.94
28P	40.81	33.02
40P	56.15	48.26

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 Betty		TOLERANCE 容許公差 .0 ± 0.30 .00 ± 0.20 ANG. ± 3°	PART NAME 品名 DIP PLUG 2.54mm X 7.62mm XXP SELECTIVE GOLD PLATING BLACK COLOR ROHS
DWG. 製圖 Betty	SCALE 比例 參考 UNIT 單位 MM	SIZE 紙張尺寸 A 4	PART NO. 料號 C3200-XXSB0000R
DATE 制表日 2012/07/28	PAGE 張數 1 OF 1	REV. 版次 A	