



- Notes:
1. Material:
Housing: Thermoplastic UL 94V-0, Black
Terminal: Copper Alloy
 2. Finished:
Terminal: 5u" Gold on Contact Area,
Gold Flash on Solder Tails,
Both over 40u" Min. Nickel Under-plated Overall

△ Dimension Information:

Amount of Pins	Dim.A	Dim.B	Dim.C	Dim.D
7	18.60	16.60	12.00	16.60
10	24.60	22.60	18.00	22.60

Recommended P.C.B. Layout
Layout Tolerance = ± 0.05mm

<p>RoHS Compliant</p>	<p>HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.</p>	
	<p>APPD. 核准 Betty</p>	<p>TOLERANCE 容許公差 X ±0.38 X° ±10° XX ±0.25 X° ±5° XXX±0.13 .XX° ±2°</p>
	<p>DWG. 製圖 Lena</p>	<p>SCALE 比例 參考 UNIT 單位 MM PAGE 張數 1 / 1</p>
	<p>DATE 制表日 2023/9/18</p>	<p>REV. 版次 A</p>
<p>PART NAME 品名 2.0MM BATTERY CONNECTOR FEMALE XXPIN RIGHT ANGLE DIP TYPE DIP LENGTH:2.2MM WITH LOCATING PEG CONTACT AREA:GOLD 5U" PLATING DIP AREA:GOLD FLASH PLATING BLACK COLOR TUBE PACKING ROHS</p>		<p>PART NO. 料號 C3479-XXRA1BYBT0R</p>