



**Material and Finish**

- 1. Housing: LCP (UL94V-0), Black.
- 2. Terminal: Sq. 0.40mm Copper Alloy, Gold Plating.

**Electrical Characteristics**

- 1. Current Rating: 1.0 Amp. Max..
- 2. Dielectric Withstand Voltage: 600V AC RMS for 60Seconds.
- 3. Insulation Resistance: 1000M Ohms Min. at 500V DC.

**Mechanical Characteristics**

- 1. Operating Temperature: -55°C ~ +105°C

**Dimensions**

Pos.	A	B	C
10	12.65	11.10	5.08
12	13.92	12.37	6.35
14	15.19	13.64	7.62
16	16.46	14.91	8.89
20	19.00	17.45	11.43
24	21.54	19.99	13.97
26	22.81	21.26	15.24
28	24.08	22.53	16.51
30	25.35	23.80	17.78
34	27.89	26.34	20.32
40	31.70	30.15	24.13
44	34.24	32.69	26.67
50	38.05	36.50	30.48
60	44.40	42.85	36.83
64	46.94	45.39	39.37
68	49.48	47.93	41.91
80	57.10	55.55	49.53
100	69.80	68.25	62.23

APPD. 核准	Betty	SCALE 比例	TOLERANCE 容許公差	PART NAME 品名
	Betty			
DWG. 製圖	Betty	UNIT 單位	ANGLE 角度	INSULATOR MATERIAL: LCP BLACK COLOR
DATE 制表日	2012/09/17	PAGE 張數	REV. 版次	ROHS
		1 OF 1	B	PART NO. 料號
				C3504-XXSGB000R

**RoHS Compliant** **HSM 玄茂科技股份有限公司**  
**HSUAN MAO TECHNOLOGY CO., LTD.**