



Specifications
 Current Rating:1Amp
 Insulation Resistance:1000MΩMin.
 Dielectric Withstanding: 300VAC
 Contact Resistance:20mΩMax.
 Operating Temperature:-40°C to +105°C
 Materials
 Contact Material: Phosphor Bronze
 Insulator Material: High Temperature Thermoplastic, UL 94V-0 LCP or the equivalent material

Recommended P.C.Board Layout (Tolerance:±0.05)

RoHS Compliant **HSM** 玄茂科技股份有限公司
 HSUAN MAO TECHNOLOGY CO., LTD.

APPD. 核准 HELEN	SCALE 比例 参考	TOLERANCE		PART NAME 品名 1.27mm X 1.27mm BOX HEADER H=11.2mm (2XXXP) SMT TYPE GOLD FLASH PLATING W/ LOCATING PEG BLACK COLOR INSULATOR MATERIAL:LCP ROHS
DWG. 製圖 ABBY		X:±5.0'	X:±0.30	
DATE 制表日 2017/01/17	UNIT 單位 MM	.X'±3.0'	.X±0.25	PART NO. 料號 C3508-XXDGBXYNR
	PAGE 張數 1 OF 1	.XX'±2.0'	.XX±0.15	
		.XXX'±1.0'	.XXX±0.10	
		SIZE. 紙張尺寸 A 4		
		REV. 版次 A		