



MATERIALS

HOUSING: HI-TEMP. PLASTIC (UL 94V-0), BLACK
 TERMINAL: PHOSPHOR BRANZE, GOLD PLATED

SPECIFICATION

CURRENT RATING: 0.5 AMP MAX
 DIELECTRIC WITHSTANDING: 300V AC FOR ONE MINUTE
 CONTACT RESISTANCE: 35m OHMS MAX
 INSULATION RESISTANCE: 500M OHMS MIN AT DC 500V
 OPERATION TEMPERATURE: -55°C~+85°C

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准	SCALE 比例 参考	TOLERANCE 容許公差	PART NAME 品名
DWG. 製圖 Betty		.0 ± 0.30 .00 ± 0.20 ANG. ± 3°	0.8mm SFP CONNECTOR SMT 90° 2X10P MATERIAL: LCP W/ PLASTIC POST (DIP L=0.9mm) BLACK COLOR REEL PACKING ROHS
DATE 制表日	UNIT 單位 M M	SIZE 紙張尺寸 A 4	PART NO.
2020/01/10	PAGE 張數 1 OF 1	REV. 版次 A	料號 C3700-20BNXR0R