



(NO.)	(Name)	(Material)
①	0.5 PH Backflip Type Housing (H=2.0)	LCP UL94V-0 Natural
②	0.5 PH Backflip Type Terminal (H=2.0)	Copper Alloy/ Gold Plating
③	0.5 PH Backflip Type Actuator (H=2.0)	LCP UL94V-0 Black
④	0.5 PH Backflip Type Fitting Nail (H=2.0)	Copper Alloy/ Tin Plating

NO POSITIONS	DIM			NO POSITIONS	DIM		
	A	B	C		A	B	C
4	1.50	2.52	5.54	24	11.50	12.52	15.54
5	2.00	3.02	6.04	25	12.00	13.02	16.04
6	2.50	3.52	6.54	26	12.50	13.52	16.54
8	3.50	4.52	7.54	28	13.50	14.52	17.54
9	4.00	5.02	8.04	30	14.50	15.52	18.54
10	4.50	5.52	8.54	32	15.50	16.52	19.54
12	5.50	6.52	9.54	34	16.50	17.52	20.54
13	6.00	7.02	10.04	36	17.50	18.52	21.54
14	6.50	7.52	10.54	40	19.50	20.52	23.54
15	7.00	8.02	11.04	45	22.00	23.02	26.04
16	7.50	8.52	11.54	50	24.50	25.52	28.54
17	8.00	9.02	12.04	54	26.50	27.52	30.54
18	8.50	9.52	12.54	60	29.50	30.52	33.54
20	9.50	10.52	13.54				

Specification:

1. Temperature range : -25° C~+85° C.
2. Rated voltage : 50V, AC/DC(=等效).
3. Contact resistance : ≤0.03Ω.
4. Insulation resistance): ≥500MΩ

**RoHS Compliant**

**HSM 玄茂科技股份有限公司**  
**HSUAN MAO TECHNOLOGY CO., LTD.**

APPD. 核准	Betty		TOLERANCE .x ±0.20 .x' ±5 .xx ±0.15 .x' ±2 .xxx ±0.10 .xx' ±1	PART NAME 品名 FPC/FFC ZIF 0.5mm PIANO TYPE SMT TYPE XXP DUAL CONTACT REEL PACKING IVORY COLOR ROHS
DWG. 製圖	Lena	SCALE 比例	UNIT 單位	PART NO. 料號
DATE 制表日	2021/1/7	參考	MM	
			PAGE 張數	
			1 OF 1	
			REV. 版本	
			B	