



NOTES: TYPICAL SPECIFICATIONS

1.0. ELECTRICAL DATE

- 1.1. FREQUENCY RANGE --- DC ... 4 GHz
- 1.2. IMPEDANC --- 50 Ohms
- 1.3. VSWR --- < 1.42
- 1.4. DIELECTRIC WITHSTANDING VOLTAGE --- 750 Vrms
- 1.5. INSULATION RESISTANCE --- 1000 Mego-Ohms
- 1.6. CENTER CONTACT RESISTANCE --- 8.0 mini-Ohms
- 1.7. OUTER CONTACT RESISTANCE --- 6.0 mini-Ohms

2.0. MECHANICAL DATA

- 2.1. COUPLING METHOD --- SNAP-ON
- 2.2. DURABILITY (MATING/UNMATING) --- 100 Cycles
- 2.3. ENGAGEMENT FORCE --- 25N max.
- 2.4. DISENGAGEMENT FORCE --- 2N min.

CODE

A		Black 9005 Radio without phantom supply
B		Cream white 9001 Radio phantom supply
C		Blue 5005 GPS
D		Bordeaux 4004 GSM cellular phone
E		Green 6002 TV1 / SDARS
F		Brown 8011 TV2 / SDARS
G		Grey 7031 Remote control keyless entry

CODE

	Violet 4003 GPS for telematics and navigation	H
	Beige 1001 Remote control parking heating	I
	Curry 1027 Radio with IF	K
	Carmine red 3002 Not defined	L
	Pastel orange 2003 Not defined	M
	Pastel green 6019 Not defined	N
	Water blue 5021 Neutral coding	Z

ITEM	NAME	MATERIAL	FINISH	Q'TY/EA
7	C-RING	SK-5	NICKEL	1
6	HOUSING	NYLON	By Code Color	1
5	LOCK RING	NYLON	By Code Color	1
4	SLEEVE	BRASS	NICKEL	1
3	FEMALE INSULATOR	TEFLON		1
2	FEMALE CONDUCTOR	PHOSPHOR BRONZE	GOLD	1
1	JACK BODY	BRASS	NICKEL	1

RoHS
Compliant

HSM 玄茂科技股份有限公司
HSUAN MAO TECHNOLOGY CO., LTD.

APPD. 核准		TOLERANCE X. ±0.25 X° ±3.0° X ±0.15 X° ±2.0° XX ±0.08 XX° ±1.0°	PART NAME 品名 FAKRA JACK CRIMPING TYPE 180° FOR CFD200 / RG-58 CONDUCTOR:PHOSPHOR BRONZE,GOLD FLASH PLATING INSULATOR MATERIAL:TEFLON 50Ω ROHS
DWG. 製圖	Betty	SCALE 比例 參考	PART NO. 料號 C4006-FSPTXA0R
DATE 制表日 2019/07/05	UNIT 單位 M M	SIZE 紙張尺寸 A 4	
	PAGE 張數 1 OF 1	REV. 版次 A	