



Material:

Housing: 30% Glass filled PBT UL94V-0.
 Contacts: Phosphor Bronze.

Electrical Characteristics:

Current Rating: 5.6 AMP.
 Dielectric Withstanding Voltage: AC 1000V For 1 minute.
 Insulator Resistance: 1000MΩ min. at DC 500V.
 Contact Resistance: 30mΩ max. at DC 100mA.
 Operating Temperature: -55°C~+105°C

***RoHS Compliant**

Pitch	Position	Rows with Contacts	x length	
			1	2
5.08mm	48	z b d	3.7	4.5
	32	z - d		
	16	z - -		

RoHS
Compliant

HSM 玄茂科技股份有限公司
 HSIUAN MAO TECHNOLOGY CO., LTD.

APPD. 核准 BETTY
 DWG. 製圖 BETTY
 DATE 制表日 2008/12/02

SCALE 比例 參考
 UNIT 單位 MM
 PAGE 張數 1 OF 1
 Tolerances
 x = ±0.5
 .x = ±0.25
 .xx = ±0.15
 SIZE. 紙張尺寸 A 4
 REV. 次 A

PART NAME 品名
 DIN41612 5.08mm DIP POWER TYPE 180° FEMALE
 XXP SELECTIVE GOLD PLATING DIP LENGTH:3.7mm
 TRAY PACKING
 PART NO. C4166-XXFXBXX0R
 料號