



Current Rating: 1 Amps  
 Insulator Resistance: 1000 Megohms min  
 Contact Resistance: 20 m ohms max  
 Dielectric Withstanding: AC 500 V  
 Operating Temperature: - 40° ~ +105° C  
 Max Processing Temp: 230° C for 60 seconds  
 260° C for 10 seconds  
 Contact Material: Phosphor Bronze  
 Insulator Material: Polyester,UL 94V-0  
 Standard:Nylon-6T  
 Finish: Tin,Gold Plated  
 Standard:Gold Flash all over

Recommended P.C. Board Hole Layout

<b>RoHS Compliant</b>		<b>HSM 玄茂科技股份有限公司</b> <b>HSUAN MAO TECHNOLOGY CO., LTD.</b>	
APPD. 核准 DWG. 製圖 DATE 制表日 2016/04/14	Hedy	TOLERANCE 容許公差 .X .XX .XXX ±0.3 ±0.20 ±0.100 SCALE 比例 參考 UNIT 單位 MM PAGE 張數 1 / 1	PART NAME 品名 1.27mm FEMALE HEADE SINGLE ROW HORIZONTAL SMT TYPE 1XXXP H:4.4mm(W:2.2mm) GOLD FLASH PLATING BLACK INSULATOR NYLON 6T UL94V-0 BOX PACKING ROHS PART NO. 料號 C4834-XXADGHD0R