



**MATERIAL**  
 HOUSING : NY6T,UL94V-0  
 CONTACT : COPPER ALLOY  
 PLATED : GOLD-FLASH  
 COLOR : BLACK

**SPECIFICATION**  
 CURRENT : 1A  
 OPERATING TEMPERATURE : -55°C TO +105°C  
 CONTACT RESISTANCE : 20 MILLIOHMS MAX  
 INSULATION RESISTANCE : 1000 MEGAOHMS MIN  
 WITHSTANDING VOLTAGE : 500V AC MIN

CONTACTS	1X21
1X2	1X22
1X3	1X23
1X4	1X24
1X5	1X25
1X6	1X26
1X7	1X27
1X8	1X28
1X9	1X29
1X10	1X30
1X11	1X31
1X12	1X32
1X13	1X33
1X14	1X34
1X15	1X35
1X16	1X36
1X17	1X37
1X18	1X38
1X19	1X39
1X20	1X40

**RECOMMENDED P. C. B LAYOUT**

RoHS Compliant		<b>HSM 玄茂科技股份有限公司</b> <b>HSUAN MAO TECHNOLOGY CO., LTD.</b>	
APPD. 核准 Betty	SCALE 比例 参考 UNIT 單位 M M PAGE 張數 1 OF 1	TOLERANCE .0=±0.38 .00=±0.25 ANG=±5° SIZE 紙張尺寸 A 4 REV. 版次 A	PART NAME 品名 2.0mm Pin Header Z Type H=1.5mm 1XXXP Gold Flash Plating C=3.0mm D=6.0mm E=6.0mm ROHS PART NO. 料號 C6116-XXAGHA00R
DATE 制表日 2015/11/26			