



Recommended P.C.Board Layout
FOR BOTTOM ENTRY
(Tolerance: ±0.05)

Specifications
 Current Rating: 2Amp
 Insulation Resistance: 1000MΩMin.
 Dielectric Withstanding Voltage: 500VAC
 Contact Resistance: 20mΩMax.
 Operating Temperature: -40°C to +105°C
 Materials
 Contact Material: Phosphor Bronze
 Insulator Material: High Temperature Thermoplastic, UL 94V-0 Nylon 6T or the equivalent material

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 HELEN	SCALE 比例 參考	TOLERANCE X* ± 5% X ± 0.30 X* ± 5% X ± 0.25 XXX* ± 1% XXX ± 0.10	PART NAME 品名 2.0mm FEMALE HEADER SINGLE ROW SMT A TYPE 1XXXP W/O LOCATING PEG INSULATOR HEIGHT: 4.3mm ROHS
DWG. 製圖 ABBY	UNIT 單位 MM	SIZE. 紙張尺寸 A 4	PART NO. 料號 C6802-XXADXCNXR
DATE 制表日 2013/03/25	PAGE 張數 1 OF 1	REV. 版次 A	