



Recommended P.C.B Layout

MATERIAL

Contact Pin : Phosphor Bronze

SPECIFICATION

Current Rate : 1 AMP

Insulation Resistance : 5000MΩMin.

Contact Resistance : 20mΩMax.

Dielectric Voltage : AC 500V for one minute

Operation Temperature : -40°C to + 105°C

| POLES | DIM A | DIM B | POLES | DIM A | DIM B |
|-------|-------|-------|-------|-------|-------|
| | | | 21 | 42.00 | 40.00 |
| | | | 22 | 44.00 | 42.00 |
| 3 | 8.00 | 4.00 | 23 | 46.00 | 44.00 |
| 4 | 8.00 | 6.00 | 24 | 48.00 | 46.00 |
| 5 | 10.00 | 8.00 | 25 | 50.00 | 48.00 |
| 6 | 12.00 | 10.00 | 26 | 52.00 | 50.00 |
| 7 | 14.00 | 12.00 | 27 | 54.00 | 52.00 |
| 8 | 16.00 | 14.00 | 28 | 56.00 | 54.00 |
| 9 | 18.00 | 16.00 | 29 | 58.00 | 56.00 |
| 10 | 20.00 | 18.00 | 30 | 60.00 | 58.00 |
| 11 | 22.00 | 20.00 | 31 | 62.00 | 60.00 |
| 12 | 24.00 | 22.00 | 32 | 64.00 | 62.00 |
| 13 | 26.00 | 24.00 | 33 | 66.00 | 64.00 |
| 14 | 28.00 | 26.00 | 34 | 68.00 | 66.00 |
| 15 | 30.00 | 28.00 | 35 | 70.00 | 68.00 |
| 16 | 32.00 | 30.00 | 36 | 72.00 | 70.00 |
| 17 | 34.00 | 32.00 | 37 | 74.00 | 72.00 |
| 18 | 36.00 | 34.00 | 38 | 76.00 | 74.00 |
| 19 | 38.00 | 36.00 | 39 | 78.00 | 76.00 |
| 20 | 40.00 | 38.00 | 40 | 80.00 | 78.00 |

| | | | | | | |
|---|-------------------|--|--|--|--|--------------------------------|
| APPD. 核准 BETTY DWG. 製圖 BETTY DATE 制表日 2008/08/06 | RoHS Compliant | | TOLERANCE 容許公差 .0 ± .00 ± ANG. ± | PART NAME 品名 2.0X2.0mm FEMALE HEADER DUAL ROW SMT H=2.7mm 2XXXP W/O LOCATING PEG ROHS LOW-LEAD | | |
| | SCALE 比例 參考 | | | | HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD. | |
| | UNIT 單位 M M | | | | | PART NO. 料號 C6804-XXBUXHNXR |
| | PAGE 張數 1 OF 1 | | | | | |