



(TYPE C)

RECOMMENDED P.C.B LAYOUT

**Material**

Insulator : LCP, glass reinforced, rated UL 94V-0  
 Contact : Phosphor Bronze

**Electrical**

Current Rating : 1 Amp  
 Contact Resistance : 30 mΩ max.  
 Insulation Resistance : 3000 MΩ min.  
 Dielectric Withstanding Voltage : 500V AC for 1minute  
 Operating Temperature : -40°C to +105°C

<b>RoHS Compliant</b>		<b>HSM 玄茂科技股份有限公司</b> <b>HSUAN MAO TECHNOLOGY CO., LTD.</b>	
APPD. 核准		<b>TOLERANCE</b> 容許公差 0 ± 0.35 .00 ± 0.25 ANG. ± 5°	<b>PART NAME 品名</b> 2.0mm FEMALE SINGLE ROW SMT C TYPE H=2.7mm 1XXXP UPPER CONTACT WITHOUT LOCATING PEG ROHS
DWG. 製圖 <i>Helen</i>	<b>SCALE</b> 比例 參考	<b>UNIT</b> 單位 MM	<b>PART NO.</b> 料號 C6804-XXCUXHNXR
DATE 制表日 2024/3/15	<b>PAGE</b> 張數 1 OF 1	<b>REV.</b> 版本 A	