



**Recommended
P.C. Board SMD Layout**

Specifications

- Current Rating : 3 Amps
- Insulator Resistance : 1000 Megohms min.
- Contact Resistance : 20 m ohms max.
- Dielectric Withstanding : AC 600V
- Operating Temperature : -40°C ~ +105°C
- Contact Material : Phosphor Bronze
- Insulator Material : Polyester, UL 94V-0
- Standard : Nylon-9T
- Contact Plated : Standard:Full Gold

RoHS
Compliant

HSM 玄茂科技股份有限公司
HSUAN MAO TECHNOLOGY CO., LTD.

APPD. 核准	SCALE 比例 參考	GENERAL TOLERANCE	PART NAME 品名
DWG. 製圖		X. ± 0.50 X. ' ± 5" .X ± 0.20 .X' ± 2" .XX ± 0.10 .XX' ± 1"	2.54mm FEMALE HEADER DUAL ROWS H:5.95mm 2XXXP SMT SIDE TYPE GOLD FLASH PLATING BLACK COLOR WITHOUT LOCATING PEG ROHS
DATE 制表日	UNIT 單位	SIZE. 紙張尺寸	PART NO.
2018/01/22	M M	A 4	料號 C6820-XXBDGHNXR
	PAGE 張數	REV. 版次	
	1 OF 1	B	