



SPECIFICATIONS

Current Rating : 1.5AMP
 Operation Temperature: -40° C to+105° C
 Contact Resistance : 20mΩ Max.
 Insulation Resistance: 1000MΩ Min.
 Withstanding Voltage : AC 500V
 Insulator Material : Polyester (UL94V-0)
 Standard: PA6T
 Contact Material : Brass
 Contact plating : Au or Sn over 50u" Ni

Dimensions list

Contacts Per row	Dimensions		Contacts Per row	Dimensions	
	A	B		A	B
2*1	2.0	0	2*16	32.0	30.0
2*2	4.0	2.0	2*17	34.0	32.0
2*3	6.0	4.0	2*18	36.0	34.0
2*4	8.0	6.0	2*19	38.0	36.0
2*5	10.0	8.0	2*20	40.0	38.0
2*6	12.0	10.0	2*21	42.0	40.0
2*7	14.0	12.0	2*22	44.0	42.0
2*8	16.0	14.0	2*23	46.0	44.0
2*9	18.0	16.0	2*24	48.0	46.0
2*10	20.0	18.0	2*25	50.0	48.0
2*11	22.0	20.0	2*26	52.0	50.0
2*12	24.0	22.0	2*27	54.0	52.0
2*13	26.0	24.0	2*28	56.0	54.0
2*14	28.0	26.0	2*29	58.0	56.0
2*15	30.0	28.0	2*30	60.0	58.0

APPD. 核准 DWG. 製圖 Betty DATE 制表日 2019/12/17	SCALE 比例 參考 UNIT 單位 MM PAGE 張數 1 OF 1	TOLERANCE X: ±0.30 X*: ±1* XX: ±0.20 XX*: ±1.05* XXX: ±0.15 XXX*: ±0.05* SIZE 紙張尺寸 A 4 REV. 版次 A	PART NAME 品名 2.0mm FEMALE HEADER H:6.35mm (Total H=7.75mm) 2XXXP SMT TYPE WITH LOCATING PEG MATERIAL:PA6T UL94V-0
			ROHS
			PART NO. 料號 C6835-XXBDXHXYR

RoHS
Compliant

HSM 玄茂科技股份有限公司
HSUAN MAO TECHNOLOGY CO., LTD.